



PERFORMANCE CONSTRUCTION PRODUCTS

Coatings - Additives - Repair - Levelling - Grouts
Sealants - Adhesives - Waterproofing



CATALOGUE

www.aftek.com.au

itls.
Performance Construction Products



ITLS-TWA is a part of the ITLS International Development Co. Ltd founded in Asia Pacific in 2008. A subsidiary of NANPAO, one of biggest chemical groups in Asia Pacific, our parent is a well-experienced company with specialized industry expertise. ITLS offers solutions utilizing the most advanced technology and designs, with the ability to deliver in a timely manner. ITLS continues to expand its development in countries worldwide aiming to offer localized services with a global perspective and technology. We integrate many of our services with the co-operation of internationally recognized companies across several continents, to maximize value and opportunity to our clients. ITLS continues to meet the needs of globalization in today's society by introducing environmentally friendly "Green products" into the market. Further more, ITLS strives to assist all our prospective partners in upgrading their solutions to create optimum results in the long and short term, for all of our mutual benefit.



NanPao Group with its turnover of over US\$400million, is one of the Top 300 manufacturers with its Headquarters in Taiwan. NanPao specializes in the manufacturing of adhesives, coatings, chemical resins and special chemical products. With production plants and office locations spread throughout Asia, including Taiwan, China (Guangzhou, Jiangsu, Fujian), Vietnam, India, Philippines, Bangladesh, Indonesia and Thailand, NanPao employs over 2,000 people.

Since the establishment of NanPao Group, we have conducted our business under the corporate motto of "Honest, Steadfast and Trustworthy". We strictly comply with our quality policy under three criteria: "Best Quality, Leading Technology and Best Service". The businesses philosophy is to establish an everlasting trust and support from our customers with our quality products and good reputation. The vision of NanPao Group is to become a major multinational company offering everyone all over the world the opportunity to know about the brands of NanPao. Our endeavor is to develop our business ; specializing in the manufacturing of special chemicals and materials with dedication to providing customers with high value products, services and solutions.



**THOMSON
WHITE
AUSTRALIA
(TWA)**

Thomson White Australia Pty Ltd (TWA) was established at the end of 1992 as the then merchants and industrial products distributor for Fosroc Expandite, at that time, a major manufacturer of specialty construction products. A manufacturer today as a part of the ITLS-TWA business, the industry has seen the AFTEK brand grow to become a market leader.

The Aftek range incorporates a broad range of highly engineered cement based products for concrete repair, flooring, and critical structural grouting applications. Epoxy resin products are an important part of Aftek's technology. High performance water based products are produced for use in brick and masonry construction.

ADHESIVES

Page 4 - 5

FLOORING

Page 6 - 7

ANCHORING

Page 8

CONSTRUCTION GROUTS

Page 8 - 9

ADMIXTURES

Page 10

CONCRETE REPAIR

Page 11-13

SURFACE COATINGS

Page 14

WOODCARE

Page 15

CONCRETE TREATMENTS

Page 16

WATERPROOFING

Page 17 - 18

SEALANTS AND FILLERS

Page 19 - 22

GUNS AND ACCESSORIES

Page 22

WOODWORKING GLUES

PVA WOODGRIP

A premium grade PVA adhesive for all woodworking and joinery applications not exposed to weather or wet conditions. Supplied in 250ml and 500ml bottles, 1 litre, 2.5 litre and 4 litre jerry cans and 20 litre cubes.

MDF ADHESIVE

Specially formulated, water based adhesive for use with medium density fibreboard. Dries clear. Available in 250 ml and 500ml bottles, 4 litre jerry cans and 20 litre cubes.

X-LINK PVA

Cross linking high strength PVA wood glue. Specially designed for exterior applications. Available in 20 litre cubes.

CONSTRUCTION ADHESIVES

ULTRAGRIP

Synthetic rubber adhesive for fixing flooring sheets and wall paneling. Tolerates moisture in timber components. Bonds to most commonly used building materials. Not suited for use on polystyrene. Available in 300ml and 850ml cartridges

ULTRAGRIP PREMIUM GRADE

High performance construction adhesive specially formulated to resist stiffening in cold weather for easy application. Excellent adhesion to damp timbers. Fills gaps up to 6mm. Supplied in 300ml and 850ml cartridges

ULTRABOND

High strength synthetic rubber based mastic adhesive suitable for use in contact with most common building materials. Safe to use on polystyrene. Available in 300ml cartridges

FOAM GRIP PU

Gun applied, foaming polyurethane adhesive suitable for bonding a wide range of commonly used construction materials such as plasterboard, particle board flooring, timber, plywood, brick, block, and concrete, AAC, CFC sheet, polystyrene, steel, some plastics and many other materials. Foamgrip PU helps reduce nail pull in flooring sheets. Supplied in 750ml aerosol cans.

CONTACT ADHESIVES

CONTACTBOND

Brushable contact adhesive for bonding decorative laminate to timber and composite sheet materials. Also suitable for bonding some rubbers such as foamed polyurethane and polychloroprene (Neoprene ®)
Available in pack sizes of 250ml, 500ml, 1 litre, 4 litre and 20 litre

FOAMGRIP

Sprayable contact adhesive with a soft, flexible glue line. Designed for use in polyurethane foam fabrication.
Available in red or neutral. Supplied in 20 litre and 200 litre drum

SPRAYGRIP

Sprayable contact adhesive for bonding decorative laminates to timber and composite sheet materials.
Can be used to bond some rubbers such as foamed polyurethane and polychloroprene.
Available in red or neutral. Supplied in 20 litre and 200 litre drums

POLYGRIP

Sprayable contact adhesive for use with all polystyrene products and components. Suitable for polystyrene foam fabrication.
Suited to coolroom panel manufacture. Coloured blue. Supplied in 20 litre and 200 litre drums.

POLYGRIP PS

Spray grade, low aggression pressure sensitive adhesive for use with polystyrene foams. Suitable for bonding styrene foam to itself & other materials such as aluminium foil, steel and some fabrics. Coloured green. Supplied in 20 litre and 200 litre drums.

EPILOX HS

A high solids, high build, floor coating system for use alone or with hard wearing aggregates to produce a skid resistant coating for concrete and steel. Can be tinted with proprietary colour packs. Use with Anti-slip Grit to provide skid resistance. Epilox HS is applied at 4-5 m² per litre. Antislip Grit is used at up to 25 kg per 4 litre kit of Epilox HS.

EPILOX SL

A heavy duty floor system based on specially selected epoxy resins, hardeners and fillers to produce a self smoothing topping for concrete. Can be tinted with proprietary Epilox Colour Packs..

CLEARKOTE SB

Is a UV resistant moisture curing polyurethane clear coating.

Clearkote SB is an aliphatic polyurethane coating that cures to form a tough, durable; trafficable coating that has extremely high abrasion resistance that may be used internal or external. Suitable for a wide range of substrates- Sports stadium floors Vinyl Flake or epoxy floor topcoat. Domestic/commercial/Industrial concrete floors. Internal and external application

DECO FLAKES

Decoflakes are coloured vinyl flakes which form part of a solvent free decorative floor coating system. Used in conjunction with Epilox HS and Clearkote SB clear. Decoflakes is one component of the total flooring system. Wide range of colours available for internal or external applications. Commercial/Industrial/Residential applications, including hospitals, kitchens, schools, food processing manufacturing. Decoflakes system is chemical & abrasion resistant.

FLOORGRAINS

Integral slip resistant finish for concrete slabs. Floor Grains are based on high quality silicon carbide. The high purity provides a more durable and slip resistant finish to concrete slabs. Supplied in 20 kg poly lined bags.

FLOORHARD E / FLOORHARD S

Monolithic integral floor hardener for increasing concrete strength during pour. Available in 20 kg poly lined bags

FLOORCOLOUR

A decorative floor hardener, based on high quality pigments, plasticisers and cement. Provides a more durable finish to concrete slabs. Available in grey, black, white and red. Supplied in 20 kg poly lined bags.

FLOORSEAL A

Acrylic resin floor sealer for concrete to provide a dustproof and more easily cleaned work environment. Ideal for warehouses, car parks and industrial applications. Applied at the rate of 5m² per litre. Available in 4 litre cans and 20 litre pails

FLOORSEAL EP

A water based low VOC epoxy floor coating for concrete and asphalt floors which provides a dust proof and oil resistant finish. It is easily applied and maintained. Available as a satin or semi gloss finish in clear or grey. Other colours can be provided to special order. Supplied in 4 litre and 16 litre kits.

ARMATITE

Water based dust proofing and surface hardening treatment for concrete floor slabs which is easily applied and maintained. Apply at the rate of 4 – 6 m² per litre. Supplied in 20 litre cubes.

EPILOX BINDER

Epoxy resin binder system for combining with selected aggregates and graded fillers to form high strength mortars ranging from pourable to paste consistency. Wide range of potential applications. Used as a primer for Epilox floor toppings Supplied in 1.5 litre, 6 litre and 30 litre kits

SYNPAVE SPORTS AND REC

SYNPAVE SPORTS & REC is a pre mixed, pre coloured water based, slip-resistant UV stable coating with excellent performance against wear and weathering, therefore providing a rejuvenated fresh and safe surface coating that is suitable for internal and external use. SYNPAVE SPORTS & REC has excellent hot tyre resistance and forms a hardwearing finish.

ECONO-PRO

A specially formulated floor leveling compound designed to achieve a smooth flat surface for application of carpet, tiles, vinyl and floating floor systems. Rapid drying accepts foot traffic in 3-4 hours. Ready to use- simply add water and mix. Can be applied from 2mm – 30mm in a single application. Floor coverings can be applied 24 hours after application

TUFF-TOP

A specially formulated floor leveling compound designed as a stand alone overlay for internal & external applications. Tru-Level Tuff Top is designed to achieve a smooth flat surface for application of tiles, vinyl timber floors and floating floor systems. Rapid drying accepts foot traffic in 3-4 hours. Accepts vehicle traffic in 4-8 hours. Ready to use- simply add water and mix. Can be applied from 5mm – 30mm in a single application. Floor coverings and coatings can be applied 24 hours after application. Hard wearing (durable, high abrasion resistant). Suitable for use on Driveways. Internal or external applications

LEVELHARD PRIMER

Levelhard Primer is a general purpose acrylic bonding agent, primer and cement modifier as part of Aftek's flooring product range. It is formulated primarily for use as a primer for Aftek Tru Level, Level Pro and Levelhard. Supplied in 5 litre bottles and 20 litre cubes

BULK FILL

A specially formulated floor leveling compound designed to achieve a high build flat surface for application of carpet and tiles. Tru Level Bulk Fill is designed to be applied in thick applications and achieve a stable crack free surface. Easy to apply. Rapid drying accepts foot traffic in 3-4 hours. Ready to use- simply add water and mix. Can be applied from 5mm – 200mm in a single application. Floor coverings can be applied 24 hours after application. Can be pumped. Economical reinstatement of uneven concrete floors. Can be top levelled with Tru Level Econo Pro to achieve a very smooth flat floor, ready to accept vinyl and timber. Supplied in 20Kg Poly lined Bags

FINE FINISH

Fast setting skim coating or feather edging compound for smoothing out ridges, gouges, scratches, cracks and filling in holes in existing uneven surfaces. Can be used to provide a smooth surface over concrete, stone, timber, ceramic tiles and terrazzo. No priming required. Accepts foot traffic and floor coverings in 30-45 min. Fine fillers allows for extremely fine repairs to the finest scratch or void. Supplied in 20Kg Poly lined Bags

RAPID PATCH

High performance polymer modified fast setting patching mortar for vertical or horizontal applications. Rapid patch is designed for creating ramps and falls prior to the application of floor coverings. Sets in 45 minutes. Can be applied from feather edge to 150mm in a single application. Fast repairs of uneven concrete floors. Heavy duty for commercial and industrial application. Underlayment mortar for flooring coverings such as vinyl, tiles, carpet timber. Supplied in 20Kg Poly lined Bags

ECONOSCREED

Econoscreed is an economical fast setting high build cementitious screed for building up areas and creating falls without shrinkage or cracking. Fast setting can be waterproofed or tiled over in 2 hours, Can be applied up to 300mm in a single application. Eliminate the need for sand and cement mixing on site. Can be applied over FC (cement sheet) internal or external. Used on balconies or wet areas such as shower recesses to achieve falls. Supplied in 20Kg Poly lined Bags

ANCHORBOLT TC

Twin cartridge, 'mix in the nozzle' epoxy injection system anchoring grout. Provides secure fixing of threaded rods and deformed bar into concrete and other solid masonry components. Supplied as a 600ml twin cartridge kit.

ANCHORBOLT EP

2 part epoxy anchoring system for positive placement of starter bars and threaded rod. Also suitable for concrete resurfacing and for use as a general purpose adhesive for bonding concrete and masonry components. Supplied in 1.5 litre and 6 litre kits

EPILOX RANGE

EPIGROUT LV

Low viscosity epoxy grout for fine crack repair. Designed to repair fine cracks in vertical, overhead or horizontal applications. May be pumped or gravity fed, depending on the application. Supplied in 300ml and 1.5 litre kits

EPIGROUT S

Pourable high strength epoxy grout for use in thicknesses less than 20 mm. Suitable for grouting base plates subject to continual vibration or high point loads, such as testing equipment, presses, bridge bearing pads and crane rail grouting. Supplied in 3 litre or 15 litre kits

EPIGROUT L

Pourable, high strength, epoxy grout for use in similar applications to EpigROUT S but where gap widths range from thicknesses of 20 mm to 50 mm. Supplied in 3.5 litre and 14 litre kits.

EPILOX BINDER

Epoxy resin system for combining with selected and graded fillers to form high strength mortars ranging from pourable to paste consistency. Wide range of potential applications. Supplied in 1.5 litre, 6 litre and 30 litre kits

EPILOX 321

High strength liquid epoxy binder for producing epoxy mortars and grouts when combined with selected, graded aggregates. Also suited for use as new to old concrete bonding agent. Supplied in 4 litre and 20 litre kits.

EPILOX 621

Non sag, high strength epoxy binder for production of paste consistency epoxy mortars for concrete repair and for grouting in starter bars and threaded rod. Supplied in kits of 4 litres

PENAFLOW CEMENTITIOUS RANGE (CLASS A)

PANEL GROUT

A Class-A construction grout based on a blend of Portland cement, high quality graded aggregates and additives, which control expansion whilst the grout is in a plastic state. Panel Grout is a general purpose grout suitable for grouting underneath precast panels and concrete sections, filling Anchor bolts, cavities, gaps, base infill's, core holes, and core filling. Shrinkage compensated. Gaseous expansion whilst in plastic state eliminates shrinkage and settlement. Non-metallic iron content eliminates staining. Can be dry packed, rammed, trowelled or poured. Pumpable for larger applications. Grouting from 20mm to 150mm in a single application

PENAFLOW GP

A class A high performance construction grout based on Portland cements, high quality graded aggregates and additives which control expansion whilst the grout is in a plastic state. High strength. Shrinkage compensated. Gaseous expansion whilst in plastic state eliminates shrinkage and settlement. High ultimate strength gain.

PENAFLOW UW

Is a high performance free flowing grout for applications requiring grouting under water or in tidal zones. PenafLOW UW is based on Portland cements, graded aggregates and chemical additives which control expansion whilst grout is in a plastic state. There is no wash out of the cement matrix and the grout has the ability to displace water when submerged or immersed in water. Suitable for use in bridge columns, dams, concrete pilings, wharf columns. Displaces water effectively. Complete void filling resulting from gaseous expansion. High strength. Exceptional flow characteristics.

PENATECH CEMENTITIOUS RANGE (CLASS C)

PENATECH HS

High strength, precision Class C grout. Non shrink dual expansion compensates for shrinkage in both the plastic and hardened state. Penatech HS complies with US Corp of Engineers Specification of non-shrink grout, CRDC 621-82A and ATSM C1107-91 (Type C). Machine base plates where critical grouting application is required. Designed for applications subject to dynamic loads and where continuous vibration is present, bridge bearing pads, crane rail sole plates, pre-cast concrete sections/ panels, anchor bolt fillings. Filling in core holes, cavities, gaps and base infill's. High performance structural grouting.

PENATECH HES

Class C high quality, free flowing non shrink, high early strength development and high ultimate strength gain cementitious grout. Penatech HES complies with US Corp of Engineers Spec CRDC 621-82A and ATSM C1107-91 for Class C grout. Cementitious grouting where high early strength is required. Heavy duty support grout beneath high load machine base plates. Precision grouting applications, anchoring bolt holes, bridge bearing pads, crane rail plates, pre-cast concrete sections, cavities, gaps and recesses. Rapid reinstatement of equipment, minimizes downtime. Grouting requiring dynamic load bearing and applications subject to continuous vibration.

PENATECH GP

General purpose high strength, precision Class C grout. Non shrink dual expansion compensates for shrinkage in both the plastic and hardened state. Penatech GP complies with US Corp of Engineers Specification of non-shrink grout, CRDC 621-82A and ATSM C1107-91 (Type C). Machine base plates where critical grouting application is required. Designed for applications subject to dynamic loads and where continuous vibration is present, bridge bearing pads, crane rail sole plates, pre-cast concrete sections/ panels, anchor bolt fillings. Filling in core holes, cavities, gaps and base infill's. High performance structural grouting.

PENATECH LA

High performance Class C micro-concrete designed for grouting large areas with no shrinking or cracking. Penatech LA is capable of grouting thicknesses up to 600mm deep in a single application. It conforms and complies with the requirements of ASTM C1107-91 and CRD-C621-82A (type C grout). Dual expansion compensates for shrinkage in the plastic and hardened state. Large volume grouting up to 600mm deep. Suitable for bridge bearing soffits and grouting requiring high ultimate strength applications subject to dynamic loads. Its low exotherm reduces cracking and shrinkage.

BMP

Brick Mortar Plasticiser. Improves the workability of brick and block mortar, extends the working time of the mortar. Also available in a special version for tropical conditions. Supplied in 5 litre jerry cans and 20 litre cubes.

MORTARLOX

Higher concentration plasticiser for use with difficult or low silt sand. Supplied in 5 litre jerry cans and 20 litre cubes

NO. 2 PASTE

Ammonium stearate based waterproofing admixture for mortar and concrete. Lines the pores in the matrix to prevent water passage by capillary action. Supplied in 5 litre jerry cans and 20 litre cubes

WATERPROOFER

Economical waterproofing admixture for brick mortar and cement render. Dosage rate of 1 litre per 40kg cement. Supplied in 1 litre and 5 litre jerry cans and 20 litre cubes

ACCELCRETE

Calcium chloride based set accelerator for unreinforced concrete. Shortens set times, particularly in cold weather. Improves early strength in concrete. Supplied in 1 litre, 5 litre bottles and 20 litre cubes

CRETEBOND

CreteBond is a versatile high grade PVA emulsion used for a wide range of applications in general construction. For bonding new to old concrete, render and hard plaster. Sealing internal concrete and masonry surfaces. As an admixture for improving the properties of mortar, render and concrete. Supplied in 5 litre and 20 litre containers.

STRUCTURAL REPAIR HB 80

High strength, high build shrinkage compensated structural repair mortar. Structural HB80 is designed to be used for vertical or horizontal applications. Structural HB80 has a high ultimate compressive strength and high abrasion resistance. The specially selected cements and polymers contained in Structural HB80 provide a mortar with strong adhesion to concrete and masonry on vertical and horizontal substrates with negligible shrinkage. Suitable for repairs requiring high compressive strength and damaged concrete panels where structural strength is required. High build repair applications 5mm to 80mm for vertical surfaces. Vertical repairs up to 160mm in small pockets or with the aid of formwork. Repairs to spalled or deteriorated concrete caused by corrosion of steel reinforcement. Repairs requiring low permeability and high resistance to chlorides and carbon dioxide. Can be applied up to 180mm in horizontal surfaces. Structural HB80 requires the addition of water only.

HIGH BUILD REPAIR MORTAR

A fine filled, light weight, cementitious mortar, specifically formulated for the repair of damaged concrete where a high build is required. Can build up to 70mm without slump. Supplied in 18 kg poly lined bags.

FAIRING COAT MORTAR

A fine filled, fast setting, cementitious mortar, specifically formulated for the repair of damaged concrete where only a thin layer is required. Ideal for repairing minor blemishes and surface defects. Supplied in 20 kg poly lined bags.

PANELPATCH LW

Fine filled, polymer modified, cementitious mortar, specifically formulated to provide cover for joiner plates in tilt slab or pre-cast construction. Panelpatch LW is also used for repair of damaged concrete. The light weight aggregates used in Panelpatch LW allows for a build up to 100mm in one application. The specially selected cements and polymers contained in Panelpatch LW provide a mortar with strong adhesion to concrete and masonry on vertical substrates with negligible shrinkage. Panelpatch LW requires the addition of water only. Panelpatch LW may be sanded to produce a smooth surface texture prior to painting or application of a render. Eliminates the need for formwork. Shrinkage compensated resulting in long term dimensional stability

FASTSET C

Quick setting cement based floor repair mortar designed to reinstate damaged concrete over larger areas and deeper holes. Provides effective, hard wearing repairs with minimal downtime. Supplied in 20 kg poly lined bags

RENDER GP

Render GP is a high performance high quality premixed acrylic polymer modified cementitious mortar for rendering ridged substrates such as brick walls, blockwork, concrete walls, AAC panel and block such as Hebel block. Interior and exterior applications.

WATERPLUG

A rapid setting, cementitious mortar, specifically formulated for sealing running water leaks in concrete structures. Supplied in 6 kg steel cans

EPILOX PM

Pre-blended epoxy mortar providing factory controlled performance. Paste consistency for ease of application. Excellent resistance to a wide range of chemicals. Provides a strong, waterproof repair. Supplied in kits of 1.5 litre and 6 litre

EPILOX FILLERS

Graded, dried quartz aggregates used with Epilox Binder, Epilox 321 and Epilox 621 to produce epoxy mortars and concretes for a wide range of repair and grouting applications. Available as F2, F4 and F6 grades
Supplied in 20kg poly lined bags.

EPISEAL

Flexible urethane modified epoxy joint sealant.

ANCHORBOLT TC

Twin cartridge, 'mix in the nozzle' epoxy injection system anchoring grout. Provides secure fixing of threaded rods and deformed bar into concrete and other solid masonry components. Supplied as a 600ml twin cartridge kit.

ANCHORBOLT EP

2 part epoxy anchoring system for positive placement of starter bars and threaded rod. Also suitable for concrete resurfacing and for use as a general purpose adhesive for bonding concrete and masonry components.
Supplied in 1.5 litre and 6 litre kits

FLOORHARD E / FLOORHARD S

Monolithic integral floor hardener for increasing concrete strength during pour.
Available in 20 kg poly lined bags

EPILOX BINDER

Epoxy resin binder system for combining with selected aggregates and graded fillers to form high strength mortars ranging from pourable to paste consistency. Wide range of potential applications. Used as a primer for Epilox floor toppings
Supplied in 1.5 litre, 6 litre and 30 litre kits

EPILOX PM

Pre-blended epoxy mortar providing factory controlled performance. Paste consistency for ease of application. Excellent resistance to a wide range of chemicals. Provides a strong, waterproof repair. Supplied in kits of 1.5 litre and 6 litre

EPICRETE

A bonding agent for new to old concrete based on specially selected epoxy resins and hardeners. Also suitable for application of epoxy mortars to damp substrates.
Supplied in 1.5 litre and 6 litre kits

EPIGROUT L

Pourable, high strength, epoxy grout for use in similar applications to Epigrout S but where gap widths range from thicknesses of 20 mm to 50 mm. Supplied in 3.5 litre and 14 litre kits.

EPIGROUT LV

Low viscosity epoxy grout for fine crack repair. Designed to repair fine cracks in vertical, overhead or horizontal applications. May be pumped or gravity fed, depending on the application.
Supplied in 300ml and 1.5 litre kits

RENDERGRIP A

Acrylic based primer for use with Fastset, Structural Repair Mortar and Fairing Coat Mortar. Supplied in 1 litre and 5 litre bottles and 20 litre cubes

RENDERGRIP B

Acrylic based thixotropic primer for use with High Build Repair Mortar Patching Mortar UL and High Build Mortar HK. Improves adhesion and reduces slump of high build mortars in vertical and overhead repairs. Supplied in 1 litre and 5 litre bottles and 20 litre cubes

RENDERGRIP S

SBR based admixture used to improve cohesive and adhesive properties of mortars and concretes. Used with Granomix to provide falls to drains. Supplied in 20 litre cubes

ZINC PRIMER

A heavy duty, zinc rich, steel protection coating formulated for use as a standalone coating or as a primer on steel reinforcing prior to application of cementitious repair materials. Available in 1 litre cans

RENDAKEE

General purpose PVA bonding agent, primer and cement modifier as part of Aftek's repair compound package. Available in 500ml, 1 litre and 4 litre bottles and 20 litre cubes.

PROTECT PRIMER

Reactive silane siloxane based penetrating sealer for concrete. Protects against the deteriorating effects of water borne chloride and sulphate ions, and cyclic wetting and drying. Supplied in 20 litre steel pails

PROTECT TOPCOAT

Acrylic based protective coating used in conjunction with Protect Primer to provide synergistic protection against carbonation in concrete structures. Supplied in 20 litre pails

WAX WRAP

Petrolatum impregnated, woven synthetic fabric tapes for protection of copper, steel and cast pipe work in above and below grade applications. Supplied in 10 metre rolls in widths from 50mm to 50mm.

ENDCHECK

Wax based emulsion for control of checking in freshly felled logs or newly milled lumber. Supplied in 20 litre pails and 200 litre drums.

VIROTUFF

Duram ViroTuff is a hard-wearing, water-based anti-slip coating that is applied by roller, brush or spray. ViroTuff is designed to provide safe and secure footing for many types of pedestrian areas such as: Walkways, Industrial floors, Domestic areas - Pool surrounds, decks, stairs, garages

VIROCOAT

Duram ViroCoat is a water based coating designed for toughness, durability, abrasion resistance and trafficability. It can be used as a general floor coating (it is smooth and not an anti-slip coating) or a wall coating where hardness and toughness is required.

SIMPLY SEAL

Aftek simplySEAL Concrete Seal is a high performance waterborne acrylic coating which provides a protective and decorative seal for concrete and masonry. Suitable for use on new and old concrete. Aftek simplySEAL dries clear but can be coloured by addition of 1 litre of Aftek simplySEAL Colour Mix per 20 litre to a range of standard or custom colours. Used as a part of the Aftek "simply" system

SIMPLY READYSEAL M.P

Aftek simplyREADYSEAL M.P. First Coat Sealer is a waterborne acrylic deep penetrating 1st coat (prep coat) sealer coat for porous inorganic and mineralised surfaces such as concrete (New and old), natural and synthetic masonry, ceramic and glass. Aftek simplyREADYSEAL M.P. dries clear but can be coloured by addition of 1 litre of Aftek simplySEAL Colour Mix per 20 litre to a range of standard or custom colours.

SIMPLYCLEAN

Aftek SimplyCLEAN Concrete Cleaner is an industrial strength, professional concrete preparation cleaner. Aftek SimplyCLEAN is a highly concentrated cleaner, designed to be diluted before use. It is specifically formulated for use as a non abrasive, neutral cleaner for sealed or unsealed concrete and masonry.

SIMPLYSTRIP

Aftek simplySTRIP Concrete Seal Stripper is an eco friendly solvent based stripper designed to dissolve and break down build up of acrylic concrete sealers and top coats.

SIMPLYSEAL COLOUR MIX

Aftek simplySEAL Colour Mix is a colour concentrate to be added to clear Aftek simplySEAL Concrete Sealer. Available in a broad range of standard colours, simplySEAL Colour Mix can also be produced in custom colours for orders of sufficient quantity.

CLEAR WATER REPELLANT

An oil based, penetrative coating and sealer for the protection of exterior timber components from the effects of the weather. Controls splitting and warping in weather exposed timbers. Ideal water repellent treatment for treated pine decking. Supplied in 2 litre, 4 litre and 10 litre tin

CLEAR WOOD PRESERVATIVE

For the protection of external joinery above ground prior to painting. An excellent "cut end" sealer for LOSP treated timber. Supplied in 2 litre, 4 litre tins and 20 litre pails.

HEAVY OIL PRESERVATIVE

A heavy duty, general purpose wood preservative which is ideal for hardwoods used in landscaping, decks, structures. Dries to a variable brown. Supplied in 2 litre, 4 litre tins and 20 litre pails.

IN GROUND PASTE

For ground line protection of hardwood posts and poles in ground contact. Also suitable for protection of exterior timbers at high risk points such as joints and interfaces. Supplied in 280gm cartridges, 3.8kg tins and 18kg pails.

WOOD TREAT LTF

Heavy duty preservative for above ground use with landscaping and fencing timbers. Controls decay in common timber species. Replaces creosote in above ground applications. Supplied in 2 litre, 4 litre tins and 20 litre pails.

NO ROT GEL

Primarily intended for remedial treatment of timber components where damp conditions prevail. For example, timber window seals, bathrooms, kitchens and other areas exposed to dampness. Dries clear. Supplied in 300 ml cartridges.

ECOSEAL

Green coloured general purpose "cut end" sealer for up to H4 and H5 level treated pine. Sold in a handy 300 gm aerosol pack.

ENSEAL CLEAR

Clear "cut end" sealer for H3 level treated pine. Particularly suited to LOSP treated exterior joinery timbers. Also supplied in a handy 300gm aerosol can.

NO ROT RODS

Unique solid rod (6 mm diameter) used for in-situ treatment of timber to prevent decay and insect attack. Ideal for joints in timber joinery.

WOODBRITE

A powerful cleaning agent for preparation of weathered timber surfaces prior to painting or staining. Non toxic, easy to use. Just add to a bucket of warm water. One 450gm jar makes up 10 litres.

WATERSHED

Short term water repellent treatment for exterior joinery. Protects against water stains prior to the application of finishes. Available in either solvent based or water based versions. Supplied in 20 litre and 200 litre pails.

CURECON A

Water based acrylic curing compound. Curecon A is a Class D, Type 1 curing compound for use on new concrete that facilitates maximum moisture retention through the curing period to maximise concrete strength & durability. Highest level of after trade compatibility. Compliance: AS3799 Supplied in 20 litre cubes, 200 litre drums and 1000 litre IBCs.

CURECON PW SMARTWAX

Class A water based wax curing compound used to retain moisture in concrete for effective curing. Used for all concrete but specifically designed for use in mass concrete structures such as roadwork, bridgework and runways. Compliance: AS3799.

CURECON PW30

High solids version of Curecon PW Smartwax, water based wax curing compound formulated to comply with NSW RTA specification. Compliance: AS3799 and NSW RTA specification.

CURECON W

Class D, water based resin curing compound used to retain moisture in concrete for effective curing. Used for all concrete surfaces exposed to the elements during the early stages of the curing process. Compliance: AS3799/NSW RTA specification Supplied in 20 litre cubes, 200 litre drums, 1000 litre IBCs and can be supplied in bulk to order.

CURECON BE

Fast drying, shower resistant water based bituminous emulsion concrete curing compound. Ideal as curing system prior to application of asphalt toppings. Compliance: AS3799/NSW RTA Specification Supplied in 20 litre cubes, 200 litre drums and 1000 litre IBCs. Can be supplied in bulk to order.

RENDACURE

Water based PVA general purpose concrete curing compound. Suitable for use with most cement based after trades. Supplied in 20 litre cubes and 200 litre drums

CURECON AA

Water based, aliphatic alcohol finishing compound designed for use on plastic (freshly poured and screeded) concrete, to reduce the evaporation of water during finishing operations. Supplied in 20 litre and 200 litre containers

STRIPFORM

Non staining form release agent for on site and precast moulds. Supplied in 20 litre and 20 litre drums

SIMPLYREVEAL

Waterbased surface set retarder for concrete, provides an attractive, decorative finish to freshly poured concrete, improves drainage and skid resistance and is also used to provide a key for new to old concrete bonding applications without the need for scabbling. Water based, variable depth of expose.

BITUFLEX

Duram Bituflex is a water-based, single pack, rubberised (latex) bituminous waterproofing membrane incorporating elastomers and reinforcing agents. It is formulated to a brushable consistency, but with sufficient body to provide a thick build-up waterproofing membrane. Bituflex dries to form a durable, flexible, elastic waterproofing membrane. Supplied in 1 litre, 4 litre and 15 litre pails

DURAM 195

Duram 195 is a single pack, liquid applied, moisture curing, self levelling, waterproofing membrane which cures to form a seamless, tough, durable, elastomeric (class 3) waterproofing membrane. Duram 195 incorporates UV stabilisers, UV absorbers and anti-oxidants to enable the product to provide greater UV protection and stability than conventional aromatic polyurethane membranes. Duram 195 bonds well to most suitably primed building substrates and is suitable for above and below ground applications. Supplied in 1 litre, 5 litre and 15 litre pails

MULTITHANE

Duram Multithane is a single pack, liquid applied, moisture curing, self leveling, waterproofing membrane which cures to form a seamless, tough, durable, elastomeric (class 3) waterproofing membrane. Multithane bonds well to most suitably primed building substrates and is suitable for above and below ground applications. Multithane Std is one of four versions within the Multithane range which include: Multithane UV; Multithane Vertical and Multithane Vertical UV. Please refer to these product data sheets for more information. Supplied in 1 litre, 4 litre and 15 litre pails

PROTEK WPU

Protek WPU is an elastomeric, one part fibre reinforced, water based polyurethane membrane used for waterproofing shower recesses, bathrooms, laundries, decks, balconies and rooftops. Suitable for internal and external applications

PROTEK WPM

Protek WPM is a waterborne waterproofing membrane designed for use under tiled finishes, capable of accommodating expected structural movement.

CRYSTOSEAL

Duram Crystoseal is a waterproofing slurry containing 'waterproofing crystals' which 'grow' into concrete surfaces to create a waterproof barrier inside the concrete. Crystoseal can often solve waterproofing problems where conventional membranes are not suitable. Crystoseal is a powder and is mixed with water and easily applied as a slurry by roller or brush. Supplied in 20kg Bags

SHOWERSEAL

Duram Showerseal is a clear (water clear) liquid sealer formulated to be applied to tiles and grout to create a water barrier against leaks. Stops leaking showers without having to remove tiles. Supplied as a kit containing all materials needed to apply Duram Showerseal. Supplied in 250ml Kit, 500ml Kits and 20 litre pails

PERMELASTIC

Bitumen emulsion, liquid applied membrane for below ground waterproofing and protection. Supplied in 4 litre cans and 20 litre pails

FERROSEAL

Cementitious metallic aggregate waterproofing coating providing a strong rigid waterproof barrier. Resistant to both positive and negative water pressure. Supplied as a kit comprising powder and liquid components. Supplied in 30kg Kits

DURAM SHOWER RECESS WATERPROOFING KIT

Duram Shower Recess Waterproofing Kit is a comprehensive kit which will allow you to waterproof your shower recess to a professional standard. It contains all the materials the user will require including: 4 litres of Durabit EF waterproofing membrane, WB primer, reinforcing fabric, leak seal tape, mastic & applicators, brushes, gloves and instructions. Supplied in 4L Kit

AZCOFLEX TR

Duram Azcoflex TR provides an excellent waterproofing membrane for areas that are subject to moderate foot traffic. Typical uses include exposed roofs, decks, balconies and plant rooms. Azcoflex TR can be coloured to provide the aesthetic appearance required. Supplied in 4 litre and 15 litre pails

DURAM S900

Duram S900 is a clear, high pH, deep penetrating siloxane waterproofing solution. S900 penetrates in to the tissue of porous substrates and creates a waterproofing barrier below the surface preventing the ingress of water. S900 is an effective waterproofing solution that stops leaks without changing the overall appearance of the surface. Supplied in 5 litre & 15 litre pails

DURAM PRIMESEAL

Duram Primeseal is a two-part, water based coating suitable for most types of porous and semi-porous surfaces. Primeseal is an excellent universal primer for all Duram waterproofing membranes, anti-slip coatings, paints and coatings. It has excellent bonding properties to most substrates and assists in the prevention of water vapour transmission from the substrate thereby minimising the risk of bubbles forming underneath membranes. Supplied in 1, 4 and 20 litre kits

WB PRIMER

Economical, general purpose, water-based primer for use on porous substrates to be top coated with water-based waterproofing membranes such as Durabit Ef, Durabit Reo, Durabit Bitumen Free, Azcoflex WPR and Azcoflex TR.

Supplied in 1 litre, 4 litre and 15 litre pails

PROTEK MOISTURE SEAL

Protek Moisture seal epoxy water vapour barrier 2 part epoxy designed as a water and vapour proof coating under waterproofing membranes and/or adhesives.

DURASCRIM

Polyester reinforcing fabric suitable for use with all Duram waterproofing membranes.

Available in: 10 meter rolls in widths of 100mm, 150mm and 300mm;

And 50m meter rolls in widths of 1metre, 100mm and 150mm.

DURAM LEAKSEAL TAPE

Duram Leak-Seal Tape is a reinforcing tape that is coated with a 1mm (approx) thick self adhesive waterproofing compound that provides a fast, economical and long term method of sealing corners & upstands, cracks and joints. Used in conjunction with the Duram waterproofing membranes, Leakseal Tape provides the ultimate in waterproofing efficiency, time, convenience and economy. Available in rolls of 15mx 80mm and 15m x 150mm.

AFTEK FLEX-PRO POLYURETHANE SEALANT

One component high performance construction joint, thixotropic moisture curing Polyurethane sealant /adhesive with high mechanical strength and excellent resistance to weathering. FLEX-PRO PU is designed for use on: construction joints, expansion joints on heavy and light precast concrete panels, expansion joints in buildings, joints in precast & tilt up concrete panels, perimeter sealing around window and door frames, curtain walls, and sealing of penetrations in walls or floors, retaining walls.

Other substrates including, anodised aluminium, steel, glass, dry timbers, some tiles, can be painted.

Class A Sealant. Total Joint movement total 50% ($\pm 25\%$)

Non Hazardous – classification (NOHSC & ADG code / Aust Safety and compensation council)

Low VOC – 35g/L.

Available in 600ml Sausages / Colours – Grey, Black, White, Bluestone, Redgum, Beige & Beach Sand).

AFTEK FLEX-PRO PRIMER

One component for use on porous substrates prior to application of Aftek Flex- Pro sealant.

AFTEK FIRE RATED SEALANT

One part fire rated non-sag acrylic joint sealant, for fire rating joints in construction commercial applications.

Sealing penetrations in plaster board, concrete floor and walls for ratings up to 4 hours.

PANEL MASTIC

Low odour, non skinning coolroom mastic. Used for sealing joints in coolroom construction.

Taint free product. Has good slump resistance at higher ambient temperatures.

HYDROLOX A6

Latex modified cementitious joint sealing compound and tile adhesive. Highly resistant to abrasion and to heavy traffic.

GAP FILLER

General purpose white acrylic mastic painters caulk. Fast drying, flexible and easily covered.

Ideal for sealing low movement joints and gaps prior to painting. Available in white only

FOAMSEAL

Bitumen impregnated polyurethane foam for sealing joints in brick, concrete and roofing iron.

Range of cross section sizes available. Supplied in 2 metre lengths

GALPRENE SB

Solvent based synthetic rubber adhesive/sealant. Ideal for sealing lap joints in sheet metal work, air conditioning ductwork and as a general purpose sealant or adhesive. Bonds to metals, glass, timber, CFC sheet, brick/block and some plastics.

GALSEAL WB

Water based synthetic resin mastic for air conditioning ductwork. Paintable as soon as the skin has formed. Excellent bond to most metals and commonly used construction materials.

CONSTRUCTION GRADE SILICONES

AFTEK WINDOW & GLASS SILICONE

Construction grade glazing silicone, acetoxycure, for use on glass to glass, windows, doors, general glazing, butt joints, anodised aluminium, fiberglass, glazed ceramic tiles. $\pm 25\%$ joint movement – Temperature range -50°C to $+150^{\circ}\text{C}$. 300gm cartridge – Colours Clear and Black.

AFTEK Xi-289 WET AREA KITCHEN & BATHROOM (NEUTRAL CURE)

Neutral cure, mould resistant silicone sealant containing an effective fungicide, designed to resist the growth of mould & mildew. For use on: fixtures and substrates in high humidity wet areas such as kitchens, bathrooms, showers, laundries, toilets, cool rooms, wash rooms and fibreglass spa units. Excellent adhesion, low odour, and good flexibility, non-slumping: can be used in vertical and overhead joints, excellent resistance to weathering, ultra-violet radiation, vibration, moisture, ozone. Joint movement $\pm 25\%$, Temperature range -45°C to $+150^{\circ}\text{C}$. Colours translucent, white and off white.

AFTEK Xi-10D

One part non slump neutral cure medium modulus extended /optimized silicone sealant. For use on: Roofing materials, roofing tiles, box gutters, spouting & flashings, coloured roofing materials, glass, windows, repairing / sealing of containers, back fill of joints, bricks, concrete and general sheet-metal work. Joint movement $\pm 25\%$, Temperature range -45°C to $+150^{\circ}\text{C}$. Colours translucent & grey.

AFTEK ROOF & GUTTER

One part neutral cure medium modulus non slump silicone sealant. For use on: All Plumbing metal roofing materials, (inc coloured roofing materials) spouting, box gutters, down pipes, flashings & capping, roof tiles, sky lights, metal water tanks, Sheet metal work, concrete & bricks, glass and some plastics. Premium Grade (100% silicone), excellent UV Stability, Low VOC, extremely flexible, tested to AS/NZS 4020 Portable Drinking Water, excellent resistance to weathering, ultra-violet radiation, vibration, moisture, ozone. Joint movement $\pm 25\%$, Temperature range -50°C to $+180^{\circ}\text{C}$. 300gm cartridge – Colours translucent, grey, black & white.

INDUSTRIAL GRADE SILICONES

AFTEK SILCON CV CARAVAN SEALANT

High performance, premium grade Low Modulus, neutral cure, silicone sealant. Specifically designed for constant high joint movement in caravans, re-locatable, cool rooms, portable homes, and where expansion joints are needed on metal panels or some plastics. This high joint movement ($+100\%$ / -50%) non staining, low shore A sealant, has in most cases self-priming onto substrates. (Substrate must be cleaned first). It is unaffected by moisture, excellent weathering and UV stability. Temperature range -50°C to $+150^{\circ}\text{C}$. 370gm cartridge -Colour white.

AFTEK INDUSTRIAL GRADE SILICONE

One part medium modulus neutral cure non slump adhesive silicone sealant. For use on: air-conditioning units, duct work, roofing and sheet metal work, manufacturing of window frames & glass weather-seal, OEM and white goods manufacturing, plant & factory maintenance. Premium Grade, excellent UV Stability, Low VOC, extremely flexible, adhesive/sealant. Joint movement $\pm 25\%$. Temperature range -50°C to $+180^{\circ}\text{C}$. 300gm cartridge – Colour Translucent. 400gm cartridge – Colour Matt Black, light grey and white.

AFTEK SILICONE CLEANER

A surface cleaner for cleaning non porous substrates (eg metals) removing of oil, grease and other soluble materials that are present on some substrates before applying Aftek silicone sealants. Some oils and greases require specific solvents to dissolve them, complete a test with AFTEK silicone cleaner, before commencement of our silicone sealant may be required.

SPECIALTY HIGH PERFORMANCE SILICONES

AFTEK Xi-168 CONSTRUCTION GLAZING

High performance premium grade neutral cure silicone. Specifically designed for shop front glazing & weatherseal applications, its superior adhesion sets it apart from other general grade silicones. Other applications - butt & fin glazing, general glazing & weatherproofing, toughened Glass Assemblies, aluminium mullions and metals. Has excellent weathering & UV stability.

Joint movement $\pm 25\%$. Temperature range -50°C $+180^{\circ}\text{C}$

300gsm cartridge - Colour translucent

400gsm cartridge Colours matt black and light grey

COMMERCIAL GLAZING

AFTEK Xi-820 ARCHITECTURAL GRADE

High performance premium grade acetoxyl rapid cure glazing silicone. Specifically designed for structural glazing (glass to glass), frameless shower screens butt & fin glazing, general glazing, toughened Glass Assemblies, aquariums, fish tanks requiring high adhesive strength & fibreglass applications, excellent weathering & UV stability. Joint movement $\pm 35\%$.

Temperature range -50°C $+200^{\circ}\text{C}$

300gsm cartridges – Colours clear and black

AFTEK Xi-860 ARCHITECTURAL GRADE

High performance premium grade neutral cure glazing silicone. Specifically designed for two sided structural glazing, butt & fin glazing, general glazing & weatherproofing, sealing of Laminated & reflective glass, sealing and adhering of mirrors & splashbacks, Toughened Glass Assemblies, aluminium mullions, metal roofing & metal water tanks, excellent weathering & UV stability. Joint movement $\pm 35\%$ - Temperature range -50°C $+200^{\circ}\text{C}$

300gsm cartridge - Colours translucent, grey, black and white.

STRUCTURAL GLAZING

AFTEK Xi-870 ARCHITECTURAL GRADE

High performance premium grade neutral cure glazing silicone. Specifically designed and meets current standards for structural glazing -four sided structural glazing & weatherseal applications. Other applications, butt & fin glazing, general glazing, weatherproofing and sealing of metal panels, sealing of Laminated & reflective glass, Toughened Glass Assemblies, aluminium mullions and metals. Has excellent weathering & UV stability. Joint movement $\pm 35\%$ - Temperature range -50°C $+200^{\circ}\text{C}$

400gsm cartridge – Colour Matt Black.

FOAM FILLER

Aerosol dispensed expanding polyurethane foam. Expands to fill uneven gaps and voids. Cures in 8 hours and can be cut, sanded and painted once cured. Expands up to 30 times original volume. Available in 290gm (300ml), 484gm (500ml) and 720gm (750ml) aerosol cans.

FOAM FILLER FIRE RETARDED GUN GRADE

Gun dispensed fire retarded expanding foam. Complies with European Standard B2 for flame retardance. Other properties are similar to Foam Filler Available in 750 ml cans

FAST FOAM PU

Aftek Fast Foam PU is a two part, moisture curing polyurethane foam sealant supplied in aerosol cans. Fast Foam PU sets rapidly with all expansion taking place in the first 15 minutes after application allowing the user to trim and finish the installation in one operation. Fast Foam PU is easy to install and will expand to fill gaps of all dimensions, and in most difficult locations

FOAM FILLER CLEANSER

Aerosol packed cleaner for use with the Aftek Foam Filler Applicator tool. Cleans uncured PU foam from the inside and outside of the applicator gun. Economical and easy to use. Available in 500ml aerosol

CAULKING GUN

High quality skeleton guns providing effortless application of sealants and adhesives. All steel construction for long service life. 300ml and 850ml versions available

SAUSAGE APPLICATOR

Closed barrel caulking gun fitted with plunger and end cap suited for efficient gunning of foil sausages.

FOAM FILLER APPLICATOR GUN

Applicator tool for dispensing Foam Filler Gun Grade and Foamgrip PU. Use Foam Filler Cleanser to clean tool after use.

EMPTY CARTRIDGES

Empty nylon cartridges complete with plunger and nozzle. Used for application of bulk sealants and adhesives.

TWIN CARTRIDGE GUN

Specially designed applicator for use with Anchorbolt TC, twin cartridge epoxy anchoring grout

BACKING ROD

Closed cell polyethylene rod for use as backing for joint sealants to control sealant depth, and to act as a bond breaker. Sizes range from 6mm diameter to 50mm diameter



CONSTRUCTION
GROUTS

CLASS A

PENAFLOW RANGE

- PENAFLOW PANEL GROUT
Multi purpose construction grout for precast panel application
- PENAFLOW GP
High performance, high strength, construction grout
- PENAFLOW LW
High performance grout for underwater applications

CLASS C

PENATECH RANGE

- PENATECH GP
General purpose, precision construction grout for use in several applications including base plates.
- PENATECH HS
High strength & high flow, precision construction grout for use in several applications including base plates.
- PENATECH HES
High Early Strength, precision construction grout for use in applications inc base plates, & Glass Balustrading.
- PENATECH LA
Micro Concrete, High Flow, deep Pour grout for soffits

CEMENTITIOUS

PENAPATCH RANGE

- HIGH BUILD REPAIR MORTAR
High Strength, High Build repair mortar for Vertical & Overhead applications
- STRUCTURAL HB80
High Strength, High Build repair mortar for Vertical & Overhead applications
- PANEL PATCH LW
Light Weight, High Build panel repair mortar for non-structural applications including filling cover plates & anchoring ports in precast panels
- FAIRING COAT
High performance fairing mortar for rectifying pin holes & imperfections in precast panels
- FAST SET C
Fast Setting, High Strength patching mortar for horizontal applications, including trafficable & industrial flooring.
- RENDER GP
General purpose render for concrete, blockwork, brickwork & masonry.
- WATERPLUG
Rapid Setting, plugging mortar for seeping & leaking concrete substrates
- FLOOR-HARD E / FLOOR-HARD S
Monolithic integral floor hardener for increasing concrete strength during pour.

CONCRETE
REPAIR

EPOXY

EPILOX RANGE

- EPILOX BINDER
Multi purpose epoxy resin system for grouts, mortars, screeds & primers
- ANCHO-BOLT EP
High performance anchoring epoxy & adhesive
- ANCHO-BOLT TC
High performance twin cartridge, anchoring epoxy & adhesive
- EPILOX PM
High performance, high build, non sag epoxy adhesive
- EPICRETE
Pre-mixed, multi purpose epoxy mortar for patch repairs.
- EPIGROUT L
High performance, High strength, flowable epoxy grout
- EPILOX LV
Low Viscosity, injection grout, for hair line & small crack width repairs
- EPISEAL
Flexible urethane modified epoxy joint sealant
- F4 & F6 EPILOX FILLERS
Specially graded aggregates for use with EpiLox range

FLOOR
PREPARATION
& LEVELLING

PENAFLOOR RANGE

- ECONO PRO
Economical, self levelling underlay for interior flooring applications under Vinyl, Tiling & Carpet
- TUFF TOP
High performance, Hard Wearing, Trafficable, Self Levelling, Exterior or Interior overlay.
- BULK FILL
Economical High Build Self Levelling underlay, used as a final levelling compound or in conjunction with Econo Pro or Tuff Top
- RAPID PATCH
Fast setting patching Mortar for building ramps & general rapid repair and re-finishment
- FINE FINISH
Skim Coat applications to achieve smooth finishes & for repair of concrete imperfections prior to floor coverings including Vinyl.
- ECONO-SCREED
High Performance screed, for configuration of shower recess with falls to drainage

PENAFLOOR EPOXY RANGE

- EPILOX SL
High performance, Self Levelling epoxy flooring system
- EPILOX HS
High Performance, High solids, epoxy coating
- DECOR LAKES
Decorative fake flooring system
- EPILOX BINDER
Multi purpose epoxy resin system for grouts, mortars, screeds & primers
- EPILOX TROWEL
High performance, Trowel Grade, epoxy flooring system
- FLOORSEAL EP
Water Based epoxy coating for concrete floors

PENAKOTE ACRYLIC RANGE

- CONCRETE SEAL
Water Based Coating and sealer for Exterior & Interior trafficable applications
- FLOORSEAL A
Solvent based Acrylic coating for Exterior & Interior trafficable applications

- VPRO COAT
Tough, water based coating designed for durability, abrasion resistance and trafficability as a general floor coating (not an anti-slip coating)

- VPROTUFF
Tough, Hard-wearing, water-based coating designed for durability, abrasion resistance and trafficability as a general floor coating with anti-slip properties.

- AZCOSEAL
Versatile solvent based acrylic sealer & protector, that provides a clear, wet-look barrier against rain water ingress

PENAKOTE URETHANE RANGE

- CLEAR-KOTE SB
Clear, water based, aliphatic polyurethane coating that cures to form a tough, durable, flexible, trafficable, abrasion and anti-scratch resistant coating in a clear gloss finish.
- ROCKTUFF
Single Component, Liquid applied Polyurethane Coating, for trafficable Exterior & Interior anti-slip textured applications. High abrasion & chemical resistance

PENAKOTE WATER REPELLANT

- S900
Silane Siloxane penetrating sealer for concrete and masonry to resist the ingress of water & salts.



Performance Construction Products

FREECALL AUSTRALIA WIDE

Tel: 1800 651 631

Fax: 1800 672 270

Head Office:
Manufacturing and Sales

Tel: (03) 9791 8211

Fax: (03) 9791 8644

250 Princes Hwy, Dandenong Victoria 3175

www.itls-twa.com.au

