Sheet1

					Transverse			Typical Wall	Weight
Product	Width	Height	Thickness	Long Reo	Reo	Cover	Concrete	Height	(+pattern)
2m STD	2000	200	75	2 x N10	N/A	30	40MPa	1.0m	73
2m Heavy Duty	2000	200	90	2 x N10	N/A	30	40MPa	2.0m	86
2m Extra Heavy Duty	2000	200	100	2 x N10	N/A	30	40MPa	3.0m	95
2m Extra Extra Heavy Duty	2000	200	120	2 x N12	N/A	30	40MPa	4.0m	114
2.4m STD	2400	200	80	2 x N12	N/A	30	40MPa	1.0m	88
2.4m Heavy Duty	2400	200	90	2 x N10	N/A	30	40MPa	2.0m	103
2.4m Extra Heavy Duty	2400	200	110	2 x N12	N/A	30	40MPa	3.0m	126
2.4m Extra Extra Heavy Duty	2400	200	140	3 x N12	N/A	30	40MPa	4.0m	156
3.0mHeavy Duty	3000	200	110	2 x N12	N/A	30	40MPa	2.0m	157
3.0m Extra Heavy Duty	3000	200	150	2 x N12	N/A	30	40MPa	3.0m	217
A+ Panel – Red	2000	800	100	4 x N16	2 x N10	40	40MPa	2.4m	389
B+ Panel – Yellow	2000	800	120	4 x N16	2 x N10	40	40MPa	4.0m	465
C+ Panel – Green	2000	800	150	6 x N16	2 x N10	40	40MPa	4.6m	579

Notes:

These are our standard products. Non Standard ones can be manufactured with different reinforcement as required. 2.4 STD is only available in plain finish. Specs have been uprated from that required by the W&G engineering.

Updated DKS 18/5/16